

SOLAR LIGHT BOLLARD ANNUAL MAINTENANCE INSTRUCTIONS

12 Monthly / Annual Maintenance Process

- 1. Use plenty of clean water to wash/rinse off any dust and grit.
- Use only a soft very wet non-textured cloth and <u>"do not"</u> use a circular motion only side-toside or up-and-down motions. Try to do the same direction every wash.
- 3. Wipe dry with a soft non-textured cloth lightly.
- 4. Allow the surface to dry before polishing.
- 5. Apply a small amount (*thumbnail size*) of Meguiar's PLASTX (*available at most automotive stores*) or similar polycarbonate polish to the dome top.
- 6. Polish with a very soft non-textured clean cloth (*or powered polisher/buff with soft material or foam pad*) the top dome surface.
- 7. Again, use side-to-side or up-and-down motions. Try to do the same direction every polish.
- 8. Wipe clean with a soft non-textured cloth after polishing
- **9.** Then spray with VuPlex or Plexus (*shake can well before use*) a light mist covering all clear polycarbonate surfaces after polishing to create an anti-static non-stick finish and protective layer and polish dry with a soft non-textured cloth.

ADVANCED CLEANING PROCESS

Cleaning of: Spray Paint, Markers and all other acidic ink and adhesive contaminants.

- Apply Ethanol (Industrial pure Alcohol) onto fine-textured soft fabric cloth and scrub off stains with pressure <u>"DO NOT"</u> use a circular motion – only side-to-side or up-and-down motions until all acidic or adhesive contaminants are removed.
- 2. Wash with a tiny amount of soft-soap or even dishwasher liquid but limit it to a couple of drops in a full bucket.
- 3. Rinse with clean water and dry with non-textured soft fabric cloth.
- **4.** Then follow above steps 3 to 9 under Annual Maintenance Process preferably using a powered polisher/buff to get a cleaner clear finish.



Please Note:

- Spray paint and other acidic liquids will slowly oxidise and weaken PC surfaces.
- The advanced cleaning process must be done immediately when this occurrence has been discovered.
- The advanced cleaning process may not restore 100% due to the PC surface having already been damaged by acidic materials.



